



1 **EC TYPE-EXAMINATION CERTIFICATE**

2 Equipment intended for use in Potentially Explosive Atmospheres Directive 94/9/EC

3 Certificate Number: Sira 03ATEX9185X

4 Equipment: RCA Pilot Solenoid Enclosures

5 Applicant: Goyen Controls

6 Address: 268 Milperra Road
Milperra
Sydney
New South Wales 2214
Australia

7 This equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

8 Sira Certification Service, notified body number 0518 in accordance with Article 9 of Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential report number R53A9662A.

9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the schedule to this certificate, has been assured by compliance with the following documents:

EN 50281-1-1:1998 (A1 and A2)

10 If the sign 'X' is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

11 This EC type-examination certificate relates only to the design and construction of the specified equipment. If applicable, further requirements of this Directive apply to the manufacture and supply of this equipment.

12 The marking of the equipment shall include the following:



II 2D

Project Number 53A9662
Date 17 June 2003
C. Index 12

C Ellaby
Certification Officer

This certificate and its schedules may only be reproduced in its entirety and without change

Sira Certification Service

Rake Lane, Eccleston, Chester, CH4 9JN, England
Tel: +44 (0) 1244 670900 Fax: +44 (0) 1244 681330
Email: exhazard@siratc.co.uk



SCHEDULE

EC TYPE-EXAMINATION CERTIFICATE

Sira 03ATEX9185X

13 DESCRIPTION OF EQUIPMENT

The RCA Pilot Solenoid Enclosures utilise aluminium enclosures that contain up to twelve solenoids fitted to one side. The solenoids have power ratings up to 28 watts and are rated at 12 V or 24 V dc or 100 up to 240 V ac, 50 or 60 Hz.

Inside the enclosures, the solenoid coils have screw clamp terminals for the supply connections. Each enclosure may have one or two cable entry points that are suitable for threaded conduit or cable glands.

14 DESCRIPTIVE DOCUMENTS

14.1	Drawing No.	Sheet	Rev.	Date	Title
	690598	1 of 1	3	8 Mar 01	Solenoid/pilot valve
	690970	1 of 1	1	16 Apr 03	RCA 3-8V8 arrangement
	690971	1 of 1	1	16 Apr 03	Label
	690972	1 of 1	1	06 May 03	Enclosure Layouts

Report No. R53A9662A

15 SPECIAL CONDITIONS FOR SAFE USE (denoted by X after the certificate number)

15.1 The solenoids shall be operated on a maximum duty cycle of 0.5 seconds on, 60 seconds off.

16 ESSENTIAL HEALTH AND SAFETY REQUIREMENTS OF ANNEX II (EHSRs)

The relevant EHSRs that are not addressed by the standards listed in this certificate have been identified and individually assessed in Report No. R53A9662A.

17 CONDITIONS OF CERTIFICATION

17.1 The use of this certificate is subject to the Regulations Applicable to Holders of Sira Certificates.

Holders of EC type-examination certificates are required to comply with the production control requirements defined in Article 8 of directive 94/9/EC.

17 June 2003

Sira Certification Service

This certificate and its schedules may only be reproduced in its entirety and without change.
Rake Lane, Eccleston, Chester, CH4 9JN, England
Tel: +44 (0) 1244 670900 Fax: +44 (0) 1244 681330
Email: exhazard@siratc.co.uk